

Installation Instructions: 5W/7W Firestay CCT LED Downlights (08187V2 / 08190V2)

Important Information

We recommend that luminaires are installed by a qualified electrician ensuring the installation complies with current IEE wiring regulations 8S7671:2018 & local building control.


- All tests should be carried out in accordance to EN 50172:2004.
- BELL will not accept responsibility for any claims arising from a poor installation.
- The light source of this luminaire is not replaceable; when the light source reaches end of life, the whole luminaire must be replaced.

Important User Advice

- The ambient room temperature should not exceed 30°C.
- Always switch off mains supply before installing.

Table 1

Downlight	Cut Out Ø
08187V2	65-70mm
08190V2	80mm



Read these instructions before installation and retain for future reference

This equipment should be installed by a competent electrician

Installation

1. Cut a square hole in the ceiling or plasterboard (see Fig 1) ensuring that it does not interfere with electrical cables or water pipes or downlights.
2. Remove bezel and adjust to required colour temperature and wattage. (see Fig 2).
3. Wire the female connector (separate in the package) to the circuit. make the necessary circuit tests. Connect the male connector (the one which is connected to the lamp) to the female connector, ensuring that they are fully 'Clicked'. (see Fig 3).
4. Fold spring clips upwards and insert fitting into the hole. (see Fig 4).
5. Release spring clips to hold fitting in place. (see Fig 5).
6. Test for correct operation.

Fig 1




Fig 2




Fig 3




Fig 4




Fig 5





Fig 6



The lamp is supplied complete with a white magnetic bezel.

Firestay CCT downlights have a choice of four color temperatures (2700k, 3000k, 4000k, 6000k). Also a choice of two wattages (5W/7W).

You can choose the colour temperature and wattage you prefer via the switches under the magnetic bezel.

To change bezels simply place the magnetic bezel on the fitting. (see Fig 61).

Insulation Coverable (IC Rated)

The lamp is designed for use with insulation material so that it does not need extra IC cage accessories.



**L: Live Brown
E: Earth Yellow/
Green N: Neutral
Blue LO loop**

This product may contain substances that can be hazardous to the environment if not disposed of properly. Electrical and electronic equipment should never be disposed of with general household waste but must be separated for its correct treatment and recovery.

Where possible recycle your packaging.

